

SSH15 THRU SSH1000

CLAMPS & PIPE SUPPORTS

SPRING HANGER



- SSH15 - SSH300, Includes pre-galvanized standard duty housing
- SSH318 - SSH1000, Includes zinc plated heavy duty housing

Part No.	Max. Load at 1" Deflection (lbs)	Solid		Dimensions			Max. Rod Diameter
		Load (lbs)	Deflection	L	W	H	
SSH15	15	28.7	1.9" 48.3	2.62" 66.6	2.25" 57.2	4.75" 120.6	1/2"
SSH30	30	48.7	1.6" 40.6				
SSH60	60	90.0	1.5" 38.1				
SSH100	100	157.2	1.6" 40.6				
SSH150	150	240.5	1.6" 40.6				
SSH200	200	269.5	1.4" 35.6				
SSH300	300	420.0	1.4" 35.6				
SSH318	318	477.0	1.5" 38.1				
SSH400	415	622.5	1.5" 38.1				
SSH500	500	705.0	1.4" 35.6				
SSH700	715	1,072.5	1.5" 38.1				
SSH1000	1060	1,166.0	1.1" 27.9				

Materials & Finishes: PG, Zinc Plated

Material Specifications			
Material	Material Code	ASTM Designation	ASTM Description
Steel:	Use Finish Code	ASTM A1011 SS GR 33.	UBS channels are accurately and carefully cold formed to size from low-carbon strip steel. 12 Ga., 14 Ga. & 16 Ga.

Finish Specifications		
Finish	Finish Code	Description
Pre-Galvanized	PG	Components are cold-rolled from pre-galvanized sheet steel manufactured to the specification requirements of ASTM A653 Grade 33 or ASTM A653 SS Grade 50. The pre-galvanized zinc coating to G-90 thickness, 0.75 MIL or 0.45 oz./sq. ft. of surface area.
Zinc Plated	-	Zinc electroplating is used to coat plain steel. The electroplating process requires that the component be immersed in a solution containing zinc ions that are deposited on the surface of the part. Electroplated zinc is shiny and smooth, and is suitable for indoor environments with low relative humidity

PROJECT INFORMATION:		APPROVAL STAMP:
Project:		
Date:	Phone:	
Architect / Engineer:		
Contractor:		
Address:		
Notes 1:		