

CHANNEL NUT WITH SPRING

SPRING NUTS AND HARDWARE

SHORT SPRING

| Part Number | Nut Size Thread | | Wt/100 pcs | Use With |
|----------------|-----------------|-----|------------|------------------------------|
| | Thread | Lbs | | |
| SN4006-1420 EG | 1/4" | -20 | 7 | CH3300, CH4000, CH4100 |
| SN4006-1420 SS | | | | |
| SN4007 EG | 5/16" | -18 | 6 | |
| SN4008 EG | 3/8" | -16 | 9 | |
| SN4010 EG | 1/2" | -13 | 8 | |
| Part Number | Nut Size Thread | | Wt/100 pcs | Use With |
| SN4012S EG | 5/8" | -11 | 10 | CH3300, CH4000, CH4100 |

Materials & Finishes: EG

| Material Specifications | | | |
|-------------------------|-----------------|-------------------------|---|
| Material | Material Code | ASTM Designation | ASTM Description |
| Steel: | Use Finish Code | ASTM A1011 SS GR 33. | UBS channels are accurately and carefully cold formed to size from low-carbon strip steel. 12 Ga., 14 Ga. & 16 Ga. |

| Finish Specifications | | |
|-----------------------|-------------|---|
| Finish | Finish Code | Description |
| Zinc Electroplated | EG | Zinc electroplating is used to coat plain steel. The electroplating process requires that the component be immersed in a solution containing zinc ions that are deposited on the surface of the part. |

| PROJECT INFORMATION: | | APPROVAL STAMP: |
|-----------------------|--------|-----------------|
| Project: | | |
| Date: | Phone: | |
| Architect / Engineer: | | |
| Contractor: | | |
| Address: | | |
| Notes 1: | | |