


GF2101 & GF2103

ANGLE FITTINGS

Wt/100pcs: 58 Lbs



Part No.	"A" Degree (rad)	"B" In (mm)
GF2101	30° 0.52	3¼ 82.6
GF2103	15° 0.26	3⅝ 84.1

Standard Dimensions for 1⅝" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: ⅝" (14.3mm); Hole Spacing - From End: 1⅜" (20.6mm); Hole Spacing - On Center: 1⅞" (47.6mm); Width: 1⅝" (41.3mm); Thickness: ¼" (6.4mm)

Materials & Finishes: EG

Material Specifications			
Material	Material Code	ASTM Designation	ASTM Description
Steel:	Use Finish Code	ASTM A1011 SS GR 33.	UBS channels are accurately and carefully cold formed to size from low-carbon strip steel. 12 Ga., 14 Ga. & 16 Ga.

Finish Specifications		
Finish	Finish Code	Description
Zinc Electroplated	EG	Zinc electroplating is used to coat plain steel. The electroplating process requires that the component be immersed in a solution containing zinc ions that are deposited on the surface of the part.

PROJECT INFORMATION:		APPROVAL STAMP:
Project:		
Date:	Phone:	
Architect / Engineer:		
Contractor:		
Address:		
Notes 1:		