


GF2863 & GF2864

FLAT PLATE FITTINGS



Part Number	Bolt Size
GF2863	$\frac{3}{8}$ "
GF2864	$\frac{1}{2}$ "

Standard Dimensions for $1\frac{5}{8}$ " (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: $\frac{9}{16}$ " (14.3mm); Hole Spacing - From End: $\frac{13}{16}$ " (20.6mm); Hole Spacing - On Center: $1\frac{7}{8}$ " (47.6mm); Width: $1\frac{5}{8}$ " (41.3mm); Thickness: $\frac{1}{4}$ " (6.4mm)

Materials & Finishes: EG

Material Specifications			
Material	Material Code	ASTM Designation	ASTM Description
Steel:	Use Finish Code	ASTM A1011 SS GR 33.	UBS channels are accurately and carefully cold formed to size from low-carbon strip steel. 12 Ga., 14 Ga. & 16 Ga.

Finish Specifications		
Finish	Finish Code	Description
Zinc Electroplated	EG	Zinc electroplating is used to coat plain steel. The electroplating process requires that the component be immersed in a solution containing zinc ions that are deposited on the surface of the part.

PROJECT INFORMATION:		APPROVAL STAMP:	
Project:			
Date:	Phone:		
Architect / Engineer:			
Contractor:			
Address:			
Notes 1:			