


## GF2900 &amp; GF2900T

## OTHER GENERAL FITTINGS

IN CHANNEL JOINERS

Wt/100pcs 20 Lbs



\* "T" for use with Slotted Channel

Set Screws included

Standard Dimensions for 1<sup>5/8</sup>" (41.3mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 9/16" (14.3mm); Hole Spacing - From End: 13/16" (20.6mm); Hole Spacing - On Center: 1 1/8" (47.6mm); Width: 1<sup>5/8</sup>"(41.3mm); Thickness: 1/4" (6.4mm)  
 Note : When used for mechanical supports, load capacities of brackets and fittings should be in compliance with the American Standard Code for Pressure Piping.

Materials &amp; Finishes: PG

Material Specifications			
Material	Material Code	ASTM Designation	ASTM Description
Steel:	Use Finish Code	ASTM A1011 SS GR 33.	UBS channels are accurately and carefully cold formed to size from low-carbon strip steel. 12 Ga., 14 Ga. & 16 Ga.

Channel Finish Specifications		
Finish	Finish Code	Description
Pre-Galvanized	PG	Components are cold-rolled from pre-galvanized sheet steel manufactured to the specification requirements of ASTM A653 Grade 33 or ASTM A653 SS Grade 50. The pre-galvanized zinc coating to G-90 thickness, 0.75 MIL or 0.45 oz./sq. ft. of surface area.

PROJECT INFORMATION:		APPROVAL STAMP:
Project:		
Date:	Phone:	
Architect / Engineer:		
Contractor:		
Address:		
Notes 1:		